IN THE SPECIFICATION

Please replace the Abstract beginning at page 15, line 1, with the following rewritten Abstract:

A device to analyze or reconstruct one or more light signals [[Ij]] coming from one or more light sources, ~~comprises:~~ including ~~means~~ a separator configured to separate the light signals [[I_j]] into at least two signals ~~I_{j1} and I_{j2}~~, at least two channels ~~V_1, V_2~~ respectively possessing a gain ~~G_1, G_2~~ and a dynamic range, ~~D_1, D_2, said~~ the channels each having at least one sensor and being adapted to ~~obtain, at~~ provide an output[[, a]] signal ~~I'_{j1}, I'_{j2} with amplitudes $A_{j1}(t)$, $A_{j2}(t)$,~~ having an amplitude, a device ~~for the processing of~~ configured to process the output signals ~~I'_{j1}, I'_{j2}~~ adapted to memorizing the amplitude ~~$A_{j1}(t)$, $A_{j2}(t)$~~ of at least one of the two signals ~~I'_{j1}, I'_{j2}~~ when ~~I'_{j1} and/or I'_{j2}~~ one of the two output signals is below a threshold value [[S_{max}]] and [[to]] determining the amplitude [[$A_j(t)$]] of the corresponding output signal. ~~I'j. Streak camera with wide range of amplitude.~~

~~Figure 1.~~